6910P

Mini Outdoor PIR



Details

- Attractive aesthetics
- 14 to 70° detection angle
- 90° pan & 45° tilt for flexible install
- Sensor module is hidden
- High dust and humidity resistance (IP65)
- 5 years warranty

6910P
Mini Outdoor PIR

Technische specificaties

General

Technology	PIR
Application type	Vægmontering
Anti masking	No
Pet immune	No
Camera	No

Detection

Max. detection range	15 m
Detection range	15 m
No. of curtains	20
Coverage (field of view)	70°
Undercrawl protection	No

Wired/wireless

Wired-wireless	Kablede

Inputs/outputs

Alarm relay characteristic	NC, signal contact 24 VAC/DC at 50 mA with an integral 25 Ohm series resistor

Electrical

Power supply value	9 to 15 VDC
Current consumption	5.5 mA

Physical

Physical dimensions	70 × 120 × 75 mm
Net weight	221 g
Shipping weight	321 g
Colour	Bronze
Material	Høj slag ABS plast med HDPE dæksel, UV stabiliseret
Mounting height	3 bis 6 m

Environmental

Operating temperature	-30 to +65°C
Environment	Udendørs
IP rating	IP65

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57