FD2705R

Analoge Beam detect., reflector principe, max. detectie afstand is 50 meter.



FD2705R

Analoge Beam detect., reflector principe, max. detectie afstand is 50 meter.

Technische specificaties

General

Addressing method	DIP Switches

Electrical

Power supply type	Loop powered

Detection

Optical wave length	880 nm

Physical

Colour	Black, Grey
Mounting type	Wall mount
Material (body)	Flame retardent ABS

Environmental

Vandal proof	No
Environment	Indoor

Regulatory

Compliancy	CE, REACH, RoHS 3, WEEE
Certification	CPR

Compatibele producten

Categorie	Referentie	Beschrijving
Detection device	FD-MB10	Montage voet voor gebruik met de FD700, FD900, FD2700 en FDR-EZ series
Detection device	OR2000	Opt. mech. Reflector voor FD705/710RVDS en FD2000/2010 beam rookdetec

KIDDE GLOBAL SOLUTIONS

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar nl.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57