ZPR868-C

Ziton series protocol, 868 Mhz, radio cluster communicator (RCC), 24 VDC

General

The ZPR868-C is a 24VDC powered wireless cluster communicator for interfacing Ziton wireless 868 MHz fire alarm devices into a ZP fire alarm system. It enables these wireless devices to be controlled directly from the ZP7 compatible CIE, and provides a seamless interface between wireless devices and the CIE.

System design

A cluster communicator comprises of a radio transceiver capable of communicating with up to 31 wireless devices. Every cluster communicator communicates directly to a ZPR868-H hub or, should direct communication not be possible, via another cluster communicator (with up to 4 hops) to the hub. This allows for full meshed networked wireless systems with multiple redundant wireless communication parts as well as longer wireless communication ranges when that is required on large sites.

Seamless addition of wireless devices

Every wireless device controlled through a cluster communicator has its own unique address with which the main fire alarm control panel communicates with it, providing the same system capabilities as directly wired devices. A full range of wireless detection and alarm devices is available, including multi-sensors capable of dual sensing heat and smoke, smoke only or heat only configurations, manual call points, notification devices (sounders & beacons) as well as input/output units.

Full flexibility

Wireless devices are featured in many fire detection and alarm systems, specified where the installation of hard wiring would be difficult or impossible to complete, decorative finishes to the interior of the protected building preclude wiring runs or where the time scales to complete installation are minimal. Cluster communicators allow the system designer full flexibility in selecting the locations of wireless devices anywhere in the system, or even allow all the filed devices in system to be wireless, up to 508 devices per CIE (or 127 devices per loop).



Details

- 24VDC supply
- 2-Way communication with up to 31 wireless devices
- Diversity transceivers allow maximum operational range
- Variable power output
- ETSI 300-220 approved
- EN54-4, 18, 25 complaint and CPR certified

ZPR868-C

Ziton series protocol, 868 Mhz, radio cluster communicator (RCC), 24 VDC

Technical specifications

General

Wireless frequency	868 MHz
Compatibility	All ZP addressable systems

Electrical

Operating voltage	18 to 30 VDC
Current consumption	22 mA @ 22 VDC (Typical) 25 mA @ 18 VDC (Maximum)

Physical

Physical dimensions	270 x 270 x 75 mm (H x W x D)
Net weight	1.8 kg
Colour	Grau (Pantone 428c)
Mounting type	Oberflächenmontage
Material	Plastik

Environmental

Operating temperature	-10 to +50°C
Storage temperature	-20 to +60°C
Relative humidity	0 to 95% noncondensing
Environment	Drinnen
IP rating	IP54

Regulatory

Certification	EN54-18, EN54-25
Approvals	EN54-4, 18, 25

Wireless

Output transmitter power	Variable 0 to 14 dBm

Compatible products

Category	Reference	Description
Interface unit	ZCC868	Configuration cable & software for 868 Mhz controllers

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 14 November 2025 - 11:33