N-IO-MBX-2

DIN Rail Module Box

General

The N-IO-MBX-2 is a surface mount enclosure designed for housing modules requiring a DIN rail mount. It's main function is to facilitate the easy installation and protection of these devices, whist keeping cabling accessible, secure and neat in the provided cable trunking inside the enclosure.



Details

- Easy installations of DIN rail mount modules on pre-fitted DIN rails
- Pre-installed cable trunking for neat cabling
- House multiple DIN units in one location in an aesthetic enclosure

N-IO-MBX-2
DIN Rail Module Box

Technical specifications

Physical

Physical dimensions	612 x 417 x 110 mm (W x H x D)
Net weight	7.3 kg
Colour	Reinweiß (RAL 9010)
Material	Metall

Environmental

Vandal proof	No
Environment	Drinnen
IP rating	IP30

Regulatory

Compliancy	CE, REACH, RoHS 3, WEEE
Certification	CE

Compatible products

Category	Reference	Description
Interface unit	KE-IO3101	Excellence series intelligent addressable 1 output unit with isolator
Interface unit	KE-IO3101-M	Excellence series intelligent addressable mains switching output unit with isolator
Interface unit	KE-IO3122	Excellence series intelligent addressable 2 input / 2 output unit with isolator
Interface unit	KE-IO3144	Excellence series intelligent addressable 4 input / 4 output unit with isolator
Interface unit	KE-IU3110	Excellence series intelligent addressable 1 input unit with isolator
Interface unit	KE-IU3111-ZME	Excellence series intelligent addressable zone monitoring unit with isolator (ext. power)

KIDDE COMMERCIAL

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 24 September 2025 - 11:08