# ACL800-RDREM-SILV

**ACL800 EM/CASI/HID Prox reader - Wiegand, HID Pass-Through, Surface mount, Silver**



# ACL800-RDREM-SILV

## ACL800 EM/CASI/HID Prox reader - Wiegand, HID Pass-Through, Surface mount, Silver

## Spécifications techniques

### System

| | |
|---|---|
| Max. reader distance to panel | 152 m |
| RTE (Request To Exit) | No |
| CSN (Card Serial Number) | Yes |
| Custom data model | No |
| No. of LEDs | 1 |
| No. of covers included | 1 |

### Technology

| | |
|---|---|
| Reader type | Nahdistanz |
| Reader operating-transmitting frequency | 125 KHz |
| Supported technology 125 kHz | EM4102, GE ProxLite/CASI Prox, HID Prox |
| Read write | No |
| SAM module embedded | No |

### Interface & connections

| | |
|---|---|
| Interface | Wiegand |
| Connector type | Zopf |
| Pigtail length | 90 cm |

### Tamper type

| | |
|---|---|
| Pry-off tamper | No |
| Opening tamper | Yes |

### Operation

| | |
|---|---|
| Stand-alone | No |
| PIN keypad | No |

### Electrical

| | |
|---|---|
| Power supply type | VDC |
| Power supply value | 5 to 24 VDC |
| Current consumption | 100 mA at 24 VDC<br>30 mA at 24 VDC |

### Physical

| | |
|---|---|
| Net weight | 120 g |
| Shipping weight | 170 g |
| Colour | Silber |
| Material | Geformtes Aluminium |
| Form factor | Mullion |
| Mounting type | Montage en surface |

### Environmental

| | |
|---|---|
| Environment | Drinnen, Draussen |
| Storage temperature | -20 to +50°C |

### Regulatory

| | |
|---|---|
| Compliancy | CE, RoHS |

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 12 November 2026 - 18:57