SMA-L-MULTI

MA SIGMA Lite - Multi, Multi-factor Bio/Card, MIFARE/MIFARE Plus/DESFIRE, 500 users, IP65, CE



SMA-L-MULTI

MA SIGMA Lite - Multi, Multi-factor Bio/Card, MIFARE/MIFARE Plus/DESFIRE, 500 users, IP65, CE

Spécifications techniques

System

RTE (Request To Exit)	No
CSN (Card Serial Number)	Yes
Custom data model	Yes

Technology

Reader type	Biometryczny
Reader operating-transmitting frequency	13.56 MHz
Supported technology 13.56 MHz	MIFARE Classic (CSN), MIFARE Classic (własne dane), MIFARE DESFire (CSN), MIFARE DESFire EV1 (CSN), MIFARE DESFire EV1 (własne dane), Mifare DESFire EV2 (CSN), MIFARE Plus (CSN), MIFARE Plus (CSN, poziom 1 i 3), NFC (CSN)
SAM module embedded	No

Biometric

Biometric type	Linie papilarne
Biometric sensor type	Optyczny

Interface & connections

Interface	Ethernet, OSDP V2, OSDP V2 Sicherer Kanal, RS-485, USB, Wiegand
Connector type	Netzwerk, Zopf

Tamper type

Pry-off tamper	No
Opening tamper	Yes

Operation

Stand-alone	Yes
PIN keypad	No

Electrical

Power supply type	VDC

Physical

Colour	Schwarz
Material	Polycarbonat
Form factor	Überdimensioniert
Mounting type	Montaż nawierzchniowy

Environmental

Vandal proof	No

Regulatory

Compliancy	CE, FCC, REACH, RoHS



En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 12 November 2026 - 18:57