# DI601

**Microprocess. PIR, buitendetector, selecteerbaar 10/20/30 m, ENgrade2 klasse 4, incert**



# DI601

## Microprocess. PIR, buitendetector, selecteerbaar 10/20/30 m, ENgrade2 klasse 4, incert

## Technische specificaties

### General

| | |
|---|---|
| Technology | PIR |
| Application type | Fixation murale |
| Anti masking | No |
| Pet immune | No |
| Camera | No |

### Detection

| | |
|---|---|
| Max. detection range | 30 m |
| Undercrawl protection | No |
| Alarm time | 5 secondes |

### Wired/wireless

| | |
|---|---|
| Wired-wireless | Kablede |

### Inputs/outputs

| | |
|---|---|
| Relay configuration | Valeurs EOL multiples |

### Physical

| | |
|---|---|
| Colour | Sølv |
| Material | Høj slag ABS plast med HDPE dæksel, UV stabiliseret |
| Mounting height | 3 à 6 m |

### Environmental

| | |
|---|---|
| Environment | Udendørs |

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar nl.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57