KE-DP3021B

Inteligentna, adresowalna podwójna czujka optyczno-termiczna z serii Excellence

General

The innovative Excellence range of intelligent addressable devices offers advanced features for reliability and peace of mind. Coupled with features for ease of installation and maintenance on new fire detection systems, it's a perfect match for exceptional overall performance.

The DP3021B is a Kidde Excellence series, graphite black addressable dual optical and heat detector. It combines a low profile design with tri-colour status indication with 360° visibility. A remote indicator output is available as standard that supports a remote indicator up to 30 m away.

Detection reliability is ensured by combining dual optical wavelengths with multiple detection angles. This allows for state-of-the-art particle size detection that differentiates between real sources of alarm, or nuisance sources such as dust and steam. As a temperature detector Class A static and rate-of-rise modes are supported to further widen the application footprint.

User friendly

All detectors are individually identified by easily setting an address through 2, modern design rotary switches. The address is a directly identified number and does not require binary or hexadecimal conversions that significantly reduces the risk of incorrect addressing.

Installation & maintenance friendly

Self-testing and drift compensation ensure safe operation with a contamination warnings provided when maintenance is needed.

All Excellence series detectors are compatible with a standard base which makes installation planning seamless and detectors easily interchangeable.

Communication protocol

An enhanced protocol ensures the overall integrity and error-free operation of the system. The Excellence series protocol provides features like CRC error checking and multiple bus cycle codes to ensure reliability between panel and device communication. The Kidde Excellence protocol still support legacy 2000 series devices in combination with the Kidde Excellence series devices.

Extended applications

A comprehensive range of additional devices and accessories complement every Excellence series device. Appart from a feature rich detector line, a comprehensive range of in- and outdoor manual call points as well as a variety of I/0 modules and accessories enrich the overall Excellence system capability.



Szczegóły

- Wyjście wskaźnika zadziałania z ochroną przeciwzwarciową zapewniającą dodatkową ochronę urządzenia
- Rozróżnianie pary i pyłu zapewniające odporność na fałszywe alarmy
- Regularne automatyczne autotesty zapewniające spokój podczas eksploatacji
- Wsparcie w zakresie temperatury statycznej i szybkiego wzrostu temperatury
- Trójkolorowy wskaźnik sygnalizujący alarm, ostrzeżenie, zwarcie, usterkę, lokalizację oraz komunikację eliminują konieczność zgadywania stanu pracy
- Widoczność wskaźnika w zakresie 360° oznacza, że nie trzeba ustawiać urządzenia w celu zapewnienia widoczności
- Nowy mechaniczny system adresowania obrotowego ułatwiający adresowanie
- Rejestrowanie zdarzeń w urządzeniu do celów diagnostycznych w razie potrzeby
- Wszystkie poziomy alarmowe posiadają certyfikat zgodności z normą EN54

KE-DP3021B

Inteligentna, adresowalna podwójna czujka optyczno-termiczna z serii Excellence

Specyfikacja techniczna

General

Status indication	Trójkolorowa dioda LED
Compatibility	Systemy Kidde Commercial Excellence
Alarm levels	11
Event log	Dostępny
Connectivity	seria Excellence, standardowe gniazdo
Addressing method	Rotary switch

Electrical

Power supply type	Alimentado por loop
Operating voltage	17 do 29 VDC
Communication voltage	4 do 11 V impulsowe
Current consumption	140 µA (spoczynek przy 24 VDC) 4,75 mA (alarm przy 24 VDC)
Terminals	6

Detection

Detection principle	Optyczne rozpraszanie światła do przodu i do tyłu / Termika
Monitoring	Alarm threshold, Contamination level, Fault
Sensitivity	Do wyboru
Coverage area	< 57 m²
Particle sensitivity range	0,1 do 0,25 dB/m ±20%
Alarm temperature (minimum)	+54°C
Rate-of-rise	Wspierane
Installation height	< 7.5 m (std) / < 9 m (zmniejszone odstępy i ocena ryzyka)
Alarm temperature (maximum)	70°C

Output

Output quantity	1
Output type and rating	Wskaźnik zadziałania
Programmable	Nie
Remote alarm output	< 8 mA

Physical

Physical dimensions	100 x 54 mm (Ø x W)
Net weight	124 g
Colour	Graphite black (RAL 9011)
Mounting type	Montagem na base
Material (body)	PC / ABS
Functional marking	Typ urządzenia
Material (contacts)	Brass
Colour	Graphite black (RAL 9011)

Environmental

Vandal proof	No
Operating temperature	-10 do +55°C
Storage temperature	-30 do +75°C
Application temperature (maximum)	+50°C
Application temperature (typical)	+25°C
Relative humidity	10 do 93% bez kondensacji
Environment	Indoor
IP rating	IP20

Regulatory

Compliancy	CE, REACH, RoHS 3, WEEE
Certification	CPR
Standards	EN54-5, EN54-7, EN54-29

Wyroby zgodne

Kategoria	Odniesienie	Opis
Detection device	KE-DB3010B	Akcesoria do inteligentnych czujek serii Excellence - gniazdo standardowe czarne

Będąc firmą innowacyjną, Kidde Global Solutions zastrzega sobie prawo do zmian w specyfikacji wyrobów bez uprzedzenia. W celu uzyskania najnowszych specyfikacji prosimy o wizytę na stronach pl/firesecurityproducts.com lub kontakt z przedstawicielem handlowym.

Last updated on 12 November 2026 - 18:57